GANTERUD

GANTERUD L3
Robust, tried and
tested technology
in a new application

Radio-controlled precision levelling

and handling. Maximises

efficiency, reduces

installation time and

increases safety



GANTERUD L3







Levelling and handling of both light and heavy objects

The GANTERUD L3 lifting yoke uses both new as well as tried and tested technology to level and handle loads efficiently and safely with a high degree of precision. The lifting yoke can handle both light and heavy objects weighing from 0 kg up to 3 tons.

Precise and wide-ranging levelling and handling of various types of objects.

The GANTERUD L3 has a reversible stroke of up to 1.5 metres per hook.

Increases productivity rate many times over

The GANTERUD L3 levels and handles the objects it is lifting easily and safely with the simple press of a button, reducing both expensive crane time and waiting times.

Strong and robust

Thanks to its robust, tried and tested technology, combined with reliable electrical operation, the GANTERUD L3 is able to operate in temperatures ranging from -20°C to +40°C in demanding environments.

Sturdy, durable and reliable

The sturdy casing, along with the IP65-rated electrical system, means that the GANTERUD L3 is easy to clean.

Radio control

With its user-friendly, IP67-rated remote control, the GANTERUD L3 is easy to operate.

Minimal service

Other than cleaning, the only thing you need to think about is charging the battery. The battery status is indicated on the yoke and, with normal use, it is sufficient to charge the battery once a week.





Technical data

Lifting capacity:	Max. 3 tons
Load imbalance capacity:	Max. 500 kg
Max. levelling length:	3 m (1.5 m in both directions)
Two levelling speeds	
Max. chain angle:	60°
, and the second	at 3 ton load
Total chain length	3 m
Chain dimensions	30.5x10 mm.
Unloaded weight	126 kg
	(incl. chain and hooks)
Height	638 mm
Width	503 mm
Depth	495 mm

Control system

Radio range:	.100 m unobstructed view	
Voltage, electric motor:	.24 VDC	
Power consumption, rest:	.50 mA	
Power consumption, max. continuous: 24 A		
Power consumption, peak	.30 A	

Certifiering

CE marked product

Environmental requirements

Operating temperature:	20°C to +40°C
Storage temperature:	20°C to +45°C
Relative humidity (RH):	0-90% during storage

Optional extra equipment

Protective cover Chain kit in other lengths Extra batteries Transport packaging

We reserve the right to alter specifications or designs without prior notification, and make reservation for any factual errors. Variations in specifications and equipment standards may occur between different geographical markets. Please contact us for more information regarding applicable product specifications and local adaptations.



Ganterud Lifting Solutions AB www.ganterud.se



Ganterud Lifting Solutions
AB is a product company
that develops and supplies
effective, reliable and
innovative lifting systems
to facilitate the handling
of materials and improve
profitability, primarily within the
construction and engineering
sectors.













Dealer:



Ganterud Lifting Solutions AB Frögatan 10 SE 653 43 Karlstad Sweden www.ganterud.se